

PRODUCT DATA SHEET

Gaboon BS1088 Marine Plywood

Description: Selected high quality, light weight, wood veneer plywood sheets primarily used in the marine

sector.

• **Specie:** Gaboon, also known as Okoume

Size: Stock Size 2440 x 1220mm

Thickness
 Construction
 and Typical
 Weights:

 4mm 3ply 5.8kg
 6mm 5ply 8.2kg

 9mm 7ply 12.8kg
 12mm 9ply 17.9kg

 15mm 11ply 20.6kg
 18mm 13ply 25.7kg

Origin: China/Europe

Colours: Pale Pink to mid-brown

• **Texture:** Even medium texture. Slightly grainy semi lustrous surface.

Grade: BS1088 for marine plywood, made with 100% Gaboon throughout.

Face veneers: A/B grade faces = clean veneer with occasional small filled end cracks

Core veneers:

B/C grade selected core veneers = peeled veneer with no internal open defects and

edge core gaps.

• **Durability:** Non durable. Note that exterior or marine plywoods are not required to be naturally durable.

Must be thoroughly sealed with preservative compounds, paints or resins

• **Density:** Average 430/460kg/m3

Stress Grade F8

• **Gluing:** Marine Phenolic formaldehyde resin, 72 hour boil test.

Commonly known as WBP (weather boil proof) or 'A' Bond.

• **Workability:** A mid-price range product reflecting high recovery utilization of resource as peeling

veneer yields high wood use to produce a light weight stable flat panel. Finishing can require medium surface grain fill levels and resin bonding is excellent. Due to the low

density nature of Gaboon this ply bends well and has a low stiffness rating

Machines, glues and works well with tungsten tip cutters to minimize fibrous end grain

Uses: All levels and areas of boat construction especially useful to keep weight to a minimum.

Also for motor homes, joinery, cabinetmaking and furniture

Good for composite panel facing. Care must be taken to ensure Gaboon is used with best

trade practices and finishing ensures no breakdown or rot occurs.

Excellent as a substrate for wood veneer or laminate overlay. The large sheet size offers

design alternatives and time saving options.