



PLYMAN

GREATER SELECTION • BETTER VALUE

PRODUCT DATA SHEET

Standard Lining Ply

- **Description:** Economical general purpose natural rotary peeled wood veneer plywood sheets.
- **Face Colour:** Pale pink to mid brown
- **Size:** 2400x1200mm
- **Thickness, Construction and Typical Weights:** Available in 6mm, 9mm, 12mm, 15mm & 18mm. Standard plywood construction. Not a multiply and will have core gaps. Poplar core. Okoume face and back.
- **Texture:** Even medium texture, slightly grainy with a semi lustrous surface.
- **Density:** Average 450kg /m³
- **Source:** China. Poplar specie is sustainably harvested. Okoume is sourced from Africa where sustainable yield forestry practices are being developed.
- **Grade:** B grade face – clean veneer with occasional end splits. CD grade core veneer – well peeled veneer allowing internal open defects and core gaps.
- **Gluing:** MR (moisture resistant) glue. Suitable for interior applications only.
- **Workability:** A very economical product designed for lining and interior paneling. Machines and glues well.
- **Durability:** Non durable, therefore standard practice of thoroughly sealing with preservative compounds, paints or resins is applicable if used in damp or wet conditions.
- **Uses:** Excellent as an economical lining plywood. Use for general lower grade interior applications. Wall linings; ceiling linings.